

Fujitsu Fault Codes

Error Detail	Indoor LED Display Flashes			Wired RC
	Operation	Timer	Economy	
Serial communication error	1	1	Continuous	11
Wired RC communication error	1	2	Continuous	12
Network communication error	1	4	Continuous	14
Check run unfinished	1	5	Continuous	15
Transmission/Peripheral connect error	1	6	Continuous	16
Refrigeration circuit address setting error	2	1	Continuous	21
Indoor unit capacity error	2	2	Continuous	22
Combination error	2	3	Continuous	23
Connection unit number error	2	4	Continuous	24
Address setting error	2	6	Continuous	26
Master/Slave unit set-up error	2	7	Continuous	27
Connection unit number error in WRC circuit	2	9	Continuous	29
Power supply interruption error	3	1	Continuous	31
Indoor PCB EPPROM error	3	2	Continuous	32
Manual auto switch error	3	5	Continuous	35
Indoor unit WRC communication error	3	10	Continuous	3A
Inlet air temp sensor error	4	1	Continuous	41
Indoor Heat-Ex middle temp sensor error	4	2	Continuous	42
Indoor unit fan motor error	5	1	Continuous	51
Indoor EEV error	5	2	Continuous	52
Drain pump error	5	3	Continuous	53
Damper error	5	7	Continuous	57
Intake grille error	5	8	Continuous	58
Indoor unit error	5	15	Continuous	5U
Outdoor PCB/communication error	6	2	Continuous	62
Inverter error	6	3	Continuous	63
Active filter/PFC circuit error	6	4	Continuous	64
Trip terminal 'L' error	6	5	Continuous	65
Display PCB/communication error	6	10	Continuous	6A
OU Discharge temp sensor error	7	1	Continuous	71
Compressor temp sensor error	7	2	Continuous	72
OU Heat-Ex liquid temp sensor error	7	3	Continuous	73
OU Ambient temp sensor error	7	4	Continuous	74
OU Suction ref temp sensor error	7	5	Continuous	75
2/3 way valve temp sensor error	7	6	Continuous	76
OU Heat sink temp sensor error	7	7	Continuous	77
Sub-cool inlet/outlet temp sensor error	8	2	Continuous	82
OU Liquid pipe temp sensor error	8	3	Continuous	83
OU current sensor error	8	4	Continuous	84
HP/LP pressure sensor/switch error	8	6	Continuous	86
OU Current trip detection	9	4	Continuous	94
Compressor rotor location detection error	9	5	Continuous	95
OU fan motor error	9	7	Continuous	97
OU fan motor 2 error	9	8	Continuous	98
4-way valve error	9	9	Continuous	99
Coil (expansion valve) error	9	10	Continuous	9A
Outdoor unit error	9	15	Continuous	9U
OU Abnormal discharge temp error	10	1	Continuous	A1
Abnormal compressor temp error	10	3	Continuous	A3
High Pressure error	10	4	Continuous	A4
Low pressure error	10	5	Continuous	A5
VRF Branch box error	13	1	Continuous	J1
8-Way Multi branch box error	13	2	Continuous	J2
Accessories	PCB LED	PCB LED		WRC
VRF RB: Cable crossed OU/RB - IU/RB	on solid	on solid	-	-
VRF RB: Coms/Main PCB error	on solid	Continuous	-	-
WRC: Incompatible IU connected	-	-	-	C0:15
WRC: Indoor - WRC comms error	-	-	-	C0:12

Error code	Contents	Causes	Confirmation
1510	"Set timer time" failed, so the command might not have been applied to the air conditioner.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
1511	"Cancel timer time" failed, so the command might not have been applied to the air conditioner.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
1520	"Weekly timer read" failed, so it might not be displayed in the app.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
1720	"Error history read" failed, so it might not be displayed in the app.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
2400	"Filter sign reset" failed, so the command might not have been applied to the air conditioner.	The smartphone terminal is not connected to the Internet. The wireless router power is not on. The air conditioner power is not on. The air conditioner is in an error state.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again. •After turning on the air conditioner power again, wait 5 to 6 minutes and then perform the operation again. •After checking the air conditioner LED status, refer to the air conditioner manual and check the status.
2710	A new account could not be created.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
2930	The air conditioner could not be found, so registration could not begin. To begin registration, your air conditioner must be selected and connected to the network.	The smartphone terminal is not connected to the Internet. The air conditioner power is not on. The air conditioner is not in AP mode.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •After turning on the air conditioner power again, wait 5 to 6 minutes and then perform the operation again. •After checking the air conditioner LED status, refer to the air conditioner manual and set the AP mode.
2931	The air conditioner could not be connected, so registration could not begin. To begin registration, your air conditioner must be selected and connected to the network.	The wireless router power is not on. The entered password is not correct.	•Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again. Enter the connection password of the selected air conditioner. Ensure that the entered password is correct.
2932	The selected router could not be connected, so registration could not begin. To begin registration, the router must be connected properly.	The wireless router power is not on. The entered password is not correct.	•Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again. Enter the connection password of the selected router. Ensure that the entered password is correct.
2933	The air conditioner was connected to the network, but registration processing failed, so the air conditioner might not have been registered to the app.	Air conditioner registration error	•Execute the instructions displayed in the message.
2934	The air conditioner was connected to the network, but registration processing failed, so the air conditioner might not have been registered to the app.	Air conditioner registration error	•Execute the instructions displayed in the message.
2935	The air conditioner was connected to the network, but registration processing failed, so the air conditioner might not have been registered to the app.	Air conditioner registration error	•Execute the instructions displayed in the message.
2936	The setting for synchronizing with the air conditioner status might not have been completed. The app can be used to operate the air conditioner, but restarting is recommended.	Air conditioner registration error	•Execute the instructions displayed in the message.
2937	The air conditioner could not be found, so registration could not begin. To begin registration, your air conditioner must be selected and connected to the network.	The air conditioner power is not on. The air conditioner is not in AP mode.	•After turning on the air conditioner power again, wait 5 to 6 minutes and then perform the operation again. •After checking the air conditioner LED status, refer to the air conditioner manual and set the AP mode.
2938	The air conditioner could not be connected, so registration cannot be started. To start registration, the same router as is connected to your mobile terminal must be selected.	A different router is selected.	•Select the same router as the router to which the mobile terminal is connected.
3010	The model name could not be registered.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.

Error code	Contents	Causes	Confirmation
3110	Could not move to selected air conditioner group.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
3111	The selected air conditioner group could not be created.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
3112	The selected air conditioner group name could not be changed.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
3113	The selected air conditioner group could not be deleted.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
3200	"LED setting ON" or "LED setting OFF" failed, so the command might not have been applied to the air conditioner.	The smartphone terminal is not connected to the Internet. The wireless router power is not on. The air conditioner power is not on. The air conditioner is in an error state.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again. •After turning on the air conditioner power again, wait 5 to 6 minutes and then perform the operation again. •After checking the air conditioner LED status, refer to the air conditioner manual and check the status.
4010	The service contact information could not be registered.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
4020	The service contact information read failed, so it might not be displayed in the app.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
4410	User information registration could not be done.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
4420	The user information read failed, so it might not be displayed in the app.	The smartphone terminal is not connected to the Internet. The wireless router power is not on. The password of using account was changed by other user.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again. Check the changed password and sign-in again.
4510	The password could not be changed.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
4520	The user information read failed, so it might not be displayed in the app.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
4610	The account could not be deleted.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
4810	The air conditioner registration could not be deleted.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
4910	The time zone could not be set.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	•Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.

Error code	Contents	Causes	Confirmation
4920	The time zone information read failed, so it might not be displayed in the app.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
5010	Mail notification could not be set.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
5020	The mail notification read failed, so it might not be displayed in the app.	The smartphone terminal is not connected to the Internet. The wireless router power is not on. The password of using account was changed by other user.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again. Check the changed password and sign-in again.
5320	The air conditioner information read failed.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
5321	The air conditioner information read failed.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
5430	The air conditioner information read failed.	The air conditioner power is not on. The air conditioner is in an error state.	<ul style="list-style-type: none"> •After turning on the air conditioner power again, wait 5 to 6 minutes and then perform the operation again. •After checking the air conditioner LED status, refer to the air conditioner manual and check the status.
5500	"Start firmware update" failed, so the command might not have been applied to the air conditioner.	The smartphone terminal is not connected to the Internet. The wireless router power is not on. The air conditioner power is not on. The air conditioner is in an error state.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again. •After turning on the air conditioner power again, wait 5 to 6 minutes and then perform the operation again. •After checking the air conditioner LED status, refer to the air conditioner manual and check the status.
5510	"Firmware automatic update ON" or "Firmware automatic update OFF" could not be set.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
5511	Firmware automatic update timer could not be set.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
5520	The air conditioner information read failed.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.
5530	The air conditioner information read failed.	The smartphone terminal is not connected to the Internet. The wireless router power is not on.	<ul style="list-style-type: none"> •Connect the mobile terminal to the Internet. •Operate it as close as possible to the router. •Check if the router power is turned on. •Check the router settings. (MAC address filter, firewall, channel setting, etc.) •Restart the router and perform this operation again.