


- Rectangular
- PVC (White)
- Uninsulated/Insulated



Channel type Flat Channel

Light non-corroding rigid PVC for fast trouble free installation available in multiple sizes to suit installation and site requirements.

Application

- Used for extraction in a ventilation system in less accessible places such as false ceilings
- Should not be installed within flooring screed

Specifications

- White PVC
- Uninsulated
- Insulated (**Insulation wall thickness 25mm**)
- Available in the following sizes:
 - 110mm x 54mm
 - 204mm x 60mm
 - 220mm x 90mm
- Available in the following lengths:
 - 1500 mm
 - 2000 mm



Dimensions											
Duct Type & Size	Dimensions External (mm)			Pressure (Pa) @ flow rate in l/s							
	H	B	L	8	13	21	29	37	45	53	61
Uninsulated 110 x 54 x 1500	54	110	1500	1.2	2.4	5.3	9.1	13.9	19.8	25.9	32
Duct Type & Size	Dimensions External (mm)			Pressure (Pa) @ flow rate in l/s							
	H	B	L	8	13	21	29	37	45	53	61
Uninsulated 204 x 60 x 1500	60	204	1500	<1	<1	1.3	2.2	3.3	4.5	5.9	7.8
Uninsulated 204 x 60 x 2000	60	204	2000	<1	<1	1.7	2.9	4.3	5.9	7.7	10.4
Insulated 204 x 60 x 1500	110	254	1500	<1	<1	1.3	2.2	3.3	4.5	5.9	7.8
Duct Type & Size	Dimensions External (mm)			Pressure (Pa) @ flow rate in l/s							
	H	B	L	60		120		180			
Uninsulated 220 x 90 x 1500	90	220	1500	1.4		4.9		10.2			
Uninsulated 220 x 90 x 2000	90	220	2000	1.9		2.6		13.6			
Insulated 220 x 90 x 1500	90	220	1500	1.4		4.9		10.2			