

Flat 90° Horizontal Bend

- Rectangular
- PVC (White)
- Uninsulated/Insulated



90 degree Horizontal Bend type Flat 90° Horizontal Bend


Light non-corroding rigid PVC for fast trouble free installation available in multiple sizes to suit installation and site requirements.

Application

- Used for extraction in a ventilation system in less accessible places such as false ceilings
- Should not be installed within flooring screed

Specifications

- White PVC
- Uninsulated
- Insulated (**Insulation wall thickness 25mm**)
- Available in the following sizes:
 - 110 x 54mm
 - 204 x 60mm
 - 220 x 90mm



Duct Type & Size		Dimensions External (mm)			Pressure (Pa) @ flow rate in l/s									
		H	B	A	8	13	21	29	37	45	53	61		
Uninsulated 110 x 54		60	152	35	2.3	9.9	21	38	64	93	124	162		
Uninsulated 204 x 60		65	260	35	0.7	1.7	4.1	8.4	13	18	25	34		
Insulated 204 x 60		160	360	35	0.7	1.7	4.1	8.4	13	18	25	34		
Duct Type & Size		Dimensions External (mm)			Pressure (Pa) @ flow rate in l/s									
		H	B	A	60	120	180							
Uninsulated 220 x 90		95	250	35	9	36	80							
Insulated 220 x 90		190	350	35	9	36	80							