

DW Ductwrap

High quality glass mineral wool roll faced with reinforced aluminium foil



Ductwrap type DW Ductwrap

Application

Cost effective thermal and acoustic insulation for metal and plastic ductwork offering improved thermal performance compared to traditional stone wool solutions.

Material

Strong, flexible high quality glass mineral roll manufactured from up to 80% recycled content and incorporates a factory applied aluminium foil facing providing an inherent vapour barrier.

Composition

Dimensions

Width x Length Thickness

1.2m x 18m - 25mm (21.6m² per roll)

1.2m x 12m - 40mm (14.4m² per roll)

1.2m x 9m - 50mm (10.8m² per roll)

In accordance with EN 822 In accordance with EN 823

Characteristics

Temperature

- Continuous service temperature from 5 °C to 150 °C.

Aluminium face should not exceed 80 °C.

Take care when using the product below ambient conditions, 100% of the vapour barrier needs to be maintained.

Certificates

- CE Marked according to EN 14303

Dimensions			
Thickness (mm)	Length (mm)	Width (mm)	Density (kg/m ³)
25	18000	1200	48
40	12000	1200	48
50	9000	1200	48

Technical Information					
Mean temp °C	10 °C	40 °C	50 °C	100 °C	120 °C