

- Daikin
- Accessory
- DMS504B51
- LonWorks Interface
- Controls



LonWorks Interface type DMS504B51

Brand

- Daikin

Product

- DIII-net LonWorks interface

Advantage

- Integrated control system for seamless connection between VRV and LonWorks BMS systems

Applicable indoor units

- All Units with F1/F2 Connection (DIII- Net)

Features

- Interface for BMS system
- Control and monitor up to 64 indoor units/groups

Specifications					
DMS504B51					
Power input	kW			0.005	
Dimensions	Unit		Height	mm	260
			Width	mm	168
			Depth	mm	50
Weight	Unit		kg	1.5	
Communication	Input terminal	Digital	Quantity	1	
			Remark	Forced shutdown	
	Protocol		Type	LonTalk	
	Transmission		Speed	Kbps	78
Ambient temperature	Operation		Medium	Twisted pair wire	
			Min.	°C	-10
			Max.	°C	50
	Storage		Min.	°C	-20
			Max.	°C	60
Ambient temperature=Relative humidity <=,%		%	95		
Installation				Mounted to indoor distribution board	
Topology				FTT-10A (Free topology)	
Power supply	Phase		1~		
	Frequency		Hz	50/60	
	Voltage		V	AC 100-240	